

[close](#) [print](#)

Brand: **Holiday Inn**
 Scheme: Revive
 Area: Guest Rooms
 Category: WindowTreatments
 Item: Drapery
 Item Code: RV-601

Vendor: Quiltcraft
 Model: See Info Below
 Description: Window Treatment
 Pattern: See Below
 Color: See Below
 Style:

Specifications:

Description: French Pleat Stationary Drapery Panel(s) with Side Return and Separate Traversing Sheer Panel(s)

Dimensions: Typical side panel finished width to be 1'-6" wide @ 200% fullness.
 Center draw Sheer.
 All dimensions and window configurations to be field verified.

Drapery Fabrication and Hardware Notes:

1. Refer to 601-A for Roller Shade.
2. All alterations to be submitted to IHG's Design & Plan Review department for written approval prior to manufacturing and purchasing.
3. Quantity: Approximately 1 pair (2 stationary side panels and two sheer panels) per window.
4. 200% fullness; overlock seams with safety stitch and surged, threaded to match predominant color of face fabric pattern.
5. Finished length to be ½" above top of carpet, and/or ½" above top of PTAC unit.
6. French pleat style: 4" double heading, 4" double hem, 1-1/2" double side hem.
7. Hardware: Mount on underside of Conrice Board (Stationary): Provide Kirsch Architrac or Equal. Use ceiling mounted track unless otherwise instructed by IHG.
8. All hardware to be corrosion proof. Drapery fabricator is responsible for the size and quantity of all hardware to be used.
9. Fabric and proposed window treatment applications must be submitted to IHG for review and approval prior to ordering.
10. Refer to Holiday Inn Window Treatment Preamble for complete specifications.
11. Drapery to be fan-folded for shipping.
12. All Products must meet or exceed applicable state and local codes.
13. All Products must be contract quality, suitable for commercial use.
14. No products shall infringe on any third party patents, copyrights, trademarks or other intellectual property rights.

Additional Notes for Sheer Fabrication and Hardware:

1. Split Draw.
2. Bottom hem to have continuous weight stringer sewn in hem.
3. 250% fullness; overlock seams with safety stitch and surged.
4. Provide off white fiberglass baton sewn into face of reinforced sheer heading no more than 54" A.F.F. Baton to be attached to carrier through crossive proof eyelet and washer to accept baton.

FABRICS: Fabric at Side Panels

Manufacturer: [Valley Forge](#)



\$ *****
 \$ *****

Vendor Contact:

Quiltcraft
 1230 East Ledbetter

Dallas, TX 75216-6988
 USA

David Pearson
 Sales Associate
 TEL: 214-376-1841
 FAX: 214-376-1852
 dpearson@quiltcraft.com

Prices above do not include taxes, shipping, or installation costs unless otherwise stated. All installed fabrics, upholstery, carpet, wall covering and other finish materials must meet local fire codes and regulations; Owner and Purchasing Agent must provide all code information to manufacturer. Fabricator and/or installer must confirm exact quantities required. Manufacturers must provide maintenance instructions.

Pattern: Free Tree
Color: Rich Brown
Width: 118"
Repeat: V: 4.5" x H: 13.25"
Content: 100% Post Consumer Recycled Polyester
Flammability: Per manufacturer, fabric meets or exceeds NFPA 701
Yardage: Approximately 4 yards per panel. Must be verified with fabricator

Sheer Fabric

Manufacturer: [Valley Forge](#)

Pattern: Sweet Magnolia Stripe
Color: Sugar
Width: 118"
Repeat: V: 16.50" x H: 0.0"
Content: 60% Polyester, 40% Post Consumer Recycled

Polyester

Flammability: Per manufacturer, fabric meets or exceeds NFPA 701
Finish: No finish applied
Yardage: Must be verified with fabricator

opening

Notes:

1. Fabric stripe to run horizontal across window
and pattern to match at center split of window.
2. **This is a sustainable product that is recyclable -**
manufacturer to provide IHG with written documentation confirming reclamation details.

General Fabric Notes:

1. All substitutions to be submitted to IHG Design & Plan Review department for written approval prior to manufacturing and purchasing.
2. Fabric must be first run goods from full bolts. Printing, dyeing, and finishing methods should be appropriate for use of fabric. Fabric should be pre-shrunk, non-fading, non-croaking, and non-pilling.
3. Must be of contract quality and suitable for commercial use.

Last Update: 2010-01-07, Original Issue: 2009-09-24 ID:5878